Lights & Lighting Accessories, VHF Antenna & Components

Signal Mate 2NM Tri-Color/Anchor **Navigation Light (3 Wire Installation)**

2 NM (nautical mile) LED navigation light, certified USCG/ ABYC A-16 & 72 COLREGS. This light is used for sailboats up to 20 meters (65 feet). The light also has a Windex illumination window for night sailing. Used by recreational vessels.



Part No.	Description
SM-TRIANC3P	. LED Tricolor / Anchor 12v w/Photodiode

OGM LED Lights







ORCA Green Marine navigation lights are rugged, reliable, and use a fraction of the amperage of traditional incandescent bulbs. OGM lights are for 12v, USCG approved with quick disconnect cables.

Part No.	Description
	LED Tricolor /Anchor Light with Strobe
OGM-LXTA-SP	LED Tricolor /Anchor Light with Photodiode & Strobe
OGM-LXA	LED Anchor Light
OGM-LXAP	LED Anchor Light with Photodiode
OGM-LX3MH	LED Steaming Light
OGM-LXBRKT-01	"L" Mounting Bracket for side mast mounting
OGM-LXBRKT-02	Mounting Bracket for top of mast mounting
OGM-SWITCHREV	Reversing Switch for Tricolor /Anchor Light
OGM-SWITCHSEL	Switch for Tricolor/Anchor Light with Strobe

Forespar Lights



Spreader/Deck Light - ML-1

Part No.	Description
FOR131300	ML-1 LED
FOR132335	LED Bottom Bulb Only ML-1 & ML-2
FOR132009	.Replacement bottom ring (Twist lock)



Combination Deck/Bow Lights - ML-2

Part No.	Description
FOR132300	ML-2, LED
FOR132325	. Top Bulb Only - LED (Steaming Light)
FOR132041	Complete Top Clear Lens



Stainless Steel Light Guard

Part No.	Description
FOR132200	Stainless Steel Chafe Guard



Scan to Browse **More Navigation Lights Online!**



Dr. LED Bulbs

The best replacement for conventional bayonet indexed light bulbs used in marine navigation lights. The first LEDs to receive USCG approval, the Polar Star series has built-in patent-pending circuitry to maintain constant 2 nautical mile visibility brightness. Operates on an input voltage range of 10VDC to 30VDC, and draws only 0.09 Amps.



Part No.	Description
DLED8001757	LED White Bulb. Fits AQ Series 40, 41, 42, 50 & 55
DLED8001450	LED Tricolor Bulb. Fits AQ Series 40, 41, 42, 50 & 55
DLED8001634	. Bi-Color Polar Star 40 (replaces 8001085 & 8001092)

Electric Wire



Made from finely stranded tinned copper for excellent corrosion resistance in a marine environment, and PVC coated for the best resistance to moisture and abrasion. Conforms to SAE specifications J1128 and J378. Intended for applications of 50v or less. Sold by the foot.

Part No.	Description
WE14/2	14 Gauge Tinned Copper Electrical Wire, Duplex
WE14/3	14 Gauge Tinned Copper Electrical Wire, Triplex
WER16/2	16 Gauge Tinned Copper Electrical Wire, Duplex, Round
WER16/3	16 Gauge Tinned Copper Electrical Wire, Triplex, Round

VHF Antenna & Components







Jack-to-Jack PL258 Coupler



PI 259 Insert for

RG58 (Small)



RG8X/58AU

Shakes, Crimp style RG8X Coax &

Coax

RG324U Large

VHFA Antenna

Part No.	Description
	Metz VHF Antenna with Bracket
COAX (FT)	RG8X Coax, Low Loss Cable, Tinned with Braid Shielding
COAXL	RG-213 Large Coax (RG8U) Cable
PL259	Coax Cable Plug - Male
PL258	Jack-to-Jack PL259 Coupler
PL259A	RG8X Cable Adapter for PL259
PL259AS	PL259 Insert for RG58 (Small)
PL259-CP	Shakes, Crimp style RG8X/58AU

Forespar Lightning™ Master Static Dissipator

Lowers the exposure to a direct lightning strike by controlling the conditions which trigger direct strike (i.e. they reduce the build-up of static ground charge and retard the formation of the ion "streamers" which complete the path for a lightning strike).

Lightweight (5.2 oz.) 21" long Dissipater mounts to the masthead and extends vertically above all other masthead equipment.

Not 100% effective in preventing a lightning strike. See Forespar.com for more information.


Part No. FOR151100





Stainless Steel Sail Tracks





Commonly used on masts and booms for high-strength sail leads. Made from type 304 Stainless Steel. Fastener holes on 2-3/4" centers.

Part No.	Description
SCH75-05-72	5/8" x 5'9-1/2"' (16mm x 1.77m) Sail Track
SCH75-05-144	5/8" x 12' (16mm x 3.6m) Sail Track
SCH74-05	End Stop for 5/8" (16mm) Sail Track
SCH74-45	Adjustable Track Stop for 5/8" (16mm) Sail Track
SCH75-07-72	
SCH75-07-144	7/8" x 12' (22mm x 3.6m) Sail Track
SCH74-02	End Stop for 7/8" (22mm) Sail Track
SCH74-42	Adjustable Track Stop for 7/8" (22mm) Sail Track

Davis Emill®

Sail Track Stops





Part No.		<u>Description</u>
DAV2350	. Round, fits most spars with round luff gro	ove50" x .875"
DAV2351	Flat, small. For spars with flat grooves	.42" x 1" x .125"
DAV2352	Flat, large. For spars with flat grooves	.75" x 1" x .125"

Davis E...

Windex 10 Sport & Windex 15

Windex® 10 Sport has a 10" vane and is 9-1/4" tall for dinghies and small keelboats. Windex® 15 has a 15" vane and is 12-3/4" tall for boats 15' and up.



Part No.	Description
	Windex® 10 Sport
DAV3150	Windex® 15
DAV1705	Deluxe Universal Masthead Mount
DAV3200	Light for Windex® 10 Sport & 15
DAV3151	Windex® 15 Replacement Vane

Rigging and Mast Boot Tape

Good rigging tape should bond only to itself - not the items being covered - be puncture resistant, and stand up well to the harsh marine environment. We stock rigging tape from both Johnson Marine and NAVTEC.



Part No.	<u>Description</u>
RIGT	Rubbaweld® Rigging Tape, White: 1" x 15' roll
RIGTB	Rubbaweld® Rigging Tape, Black: 1" x 15' roll
MASTT100	Rubbaweld® Mast Boot Tape, White: 4" x 10'

Windblown Mastboots

Flexible rubber with aggressive adhesive backing, UV stable and durable. 5" wide and 1/10 of an in thick. Tape is applied from the bottom up in a shingle like manner. Once in place it forms a one-piece custom fitted boot. When it's time for removal, just slit the boot with a knife or razor and peel it away.



2	Part No. Description
3	MAST40 Designed to fit boats up to 40'*
j	MAST60 Designed to fit boats up to 60'*
	*Boat lengths are a general guide. If you have an unusually large mast please con-
=	tact us for recommendations.

Shroud Cleats

Non-corrosive stainless steel construction, compatible with stainless steel rigging. Easily attached to 5/32" through 3/8" diameter wire or rod. Ideal for flag halyards with an eye for attaching a snap shackle.

Part No.

J40-518

Folding Mast Steps

Polished, clear anodized cast #356 T-6 aluminum. Step has 5" tread width; when closed, extends 1-1/2" from mast. Includes nylon adjusting screw to eliminate rattle when in the closed position.

Part No.

SD328030 ... Price for 24 steps or less

*Discount available for 25 steps or more.

Spartite®

The Spartite® Mast Wedge Replacement System kit is the perfect solution to secure and seal a mast at deck level. Spartite® helps keep the mast up and the water out! Spartite® is a pre-measured two-part polymer poured into the cavity between the mast and the partners while the mast is in the boat. Comes with complete instructions and materials to build a simple mold out of even the most complex partners or mast collar. Spartite® makes a



one-piece perfect fitting mast chock that replaces archaic wedges.

Part No.	Description	
SPARTS	Small Spartite® Kit for boats up to 40'*	
SPARTL	Large Spartite® Kit for boats over 40'*	
*Lengths are a general guide. If you have an unstayed rig or an unusually large gap		
(over 1") between your mast and collar please nurchase the large kit		

Spreader Boots

Durable vinyl spreader boots available for both round and flat spreaders. Easily installed with rigging tape. (See RIGT)



Part No.	Description
SBFL	Large Spreader Boot for Flat Spreaders (pr.) 3-1/4" X 1"
SBRS	Small Spreader Boot for Round Spreaders (pr.) To 1/8" Wire
SBRM	Med. Spreader Boot for Round Spreaders (pr.) To 3/16" Wire
SBRL	Large Spreader Boot for Round Spreaders (pr.) To 1/4" Wire

Edson Leather Spreader Boots

Leather spreader kits from Edson Marine include two pre-punched Dove Gray Leather Spreader Boot Covers, heavy waxed polyester thread for lacing, hand-stitching needle, and instructions.





Part No.	<u>Description</u>
ED1401-1	Edson Leather Spreader Boot Kit for 1" Spreaders (pr.)
ED1401-3	. Edson Leather Spreader Boot Kit for 3" Spreaders 9pr.)

Seizing Wire - Type 302/304

Used for applications such as fixing spreader ends to shrouds, and locking shackle pins.

Part No.	Description
LOOSSLWQ032	. Seizing Wire, SS, .032" Dia. x 91'
LOOSSLWQ041	. Seizing Wire, SS, .041" Dia. x 55'
WSEIZ02Sei	zing Wire, SS, 1/16" 1x7, per foot

