



Whisker Pole Size Recommendations

Boat Length:	Working Jib		Genoa	
	Light to Mod. Air	Mod. to Heavy Air	Light to Mod. Air	Mod. to Heavy Air
Up to 16'	ADJ 4'-8'	ADJ 6'-12'	ADJ 6'-12'	HD 6'-12'
Up to 22'	ADJ 6'-12'	HD 6'-12'	HD 6'-12'	LC 8'-14'
Up to 25'	HD 6'-12'	HD 6'-12'	ADJ 7'-15'	ADJ 7'-15'
Up to 28'	ADJ 7'-15'	ADJ 7'-15'	ADJ 7'-15'	LC 10'-18'
Up to 33'	LC 10'-18'	LC 10'-18'	LC 10'-18'	LC 12'-22'
Up to 35'	LC 12'-22'	LC 12'-22'	LC 12'-22'	LC 13'-24'
Up to 46'	LC 13'-24'	LC 13'-24'	LC 13'-24'	LC 15'-27'
Up to 50'	LC 15'-27'	LC 15'-27'	LC 15'-27'	
Custom 50' and Over	Please contact us regarding poles of this size.			



Sailing Services stocks a full range of Forespar® whisker poles, as well as mil. spec aluminum tubing, end fittings, and mast mounting accessories. We will build custom spinnaker poles to your specifications, and assist you with the design of pole lift and storage solutions. Carbon poles are available by special order. Call us for details.

Small Telescoping Poles

Twist lock includes end fittings, and plastic mast pad eye with stainless steel screws.



Part No.	Model No.	Description
FOR404000	ADJ 4-8	Telescopes from 53" to 93" / 3 lbs.
FOR404100	ADJ 4-8 DL	With latch fittings on both ends
FOR406000	ADJ 6-12	Telescopes from 72" to 134" / 3 lbs.
FOR406100	ADJ 6-12 DL	With latch fittings on both ends

Heavy Duty Telescoping Poles



Heavy duty two-section and three-section aluminum spars can be extended to lengths up to 17' and securely locked into position by an internal twist lock device. Poles feature self-latching Ultra Series fittings on the inboard and outboard ends.

Part No.	Model No.	Description
FOR406300	HD 6-12-DL	Telescopes from 79" to 138", 8 lbs.
FOR407101	ADJ 7-15-DL	Three sections, 83" to 169", 8 lbs.
FOR304015	HD 6-12 DL	Replacement inboard end fitting for ADJ 6-12
FOR304018	HD 6-12 DL	Replacement outboard end fitting for ADJ 6-12
FOR304057	ADJ 7-15 DL	Replacement inboard end fitting for ADJ 7-15

Tri-Reacher™ Whisker Pole

For boats 35'-42' LOA, the new Tri-Reacher™ whisker pole has been developed specifically for use with Asymmetrical/Gennaker sails. This 3-part telescoping whisker pole used with these sails will allow deeper sailing angles and eliminate the need for constant jibing downwind. Collapses to 8', extends to 21'.



Part No.	Description	SWL	Pole Size
FOR408200	Whisker Pole	22 lbs	8' - 21'

Aluminum Tubing

Clear anodized to military specification (triple commercial). Prime marine alloy 6063-T6. Tubing sold in stock lengths.

Part No.	O.D.	Length	Wall	I.D.	Wt./Ft.
FOR500015	1-1/4"	20'	0.050"	1.150"	.22 lbs.
FOR500018	1-1/2"	22' 6"	0.065"	1.370"	.35 lbs.
FOR301005	1-1/2"	7' 6"	0.065"	1.370"	.35 lbs
FOR500020	2"	21' 6"	0.065"	1.870"	.47 lbs
FOR408003	2"	7' 2"	0.065"	1.870"	.47 lbs
FOR401004	2"	9' 1"	0.065"	1.870"	.47 lbs
FOR301006	2"	9' 4"	0.065"	1.870"	.47 lbs
FOR301058	2-1/2"	20' 2"	0.083"	2.334"	.74 lbs
FOR301056	2-1/2"	9'	0.083"	2.334"	.74 lbs
FOR301057	2-1/2"	11' 2"	0.083"	2.334"	.74 lbs
FOR301065	3"	11' 2"	0.083"	2.835"	1.00 lbs
FOR301072	3"	12' 2"	0.083"	2.835"	1.00 lbs
FOR301019	3"	13'	0.083"	2.835"	1.00 lbs
FOR301063	3"	16'	0.083"	2.835"	1.00 lbs
FOR301030	3"	23' 4"	0.083"	2.835"	1.00 lbs
FOR301061	3-1/2"	24' 4"	0.120"	3.260"	1.50 lbs
FOR403004	3-1/2"	12' 2"	0.120"	3.260"	1.50 lbs
FOR301059	3-1/2"	14'	0.120"	3.260"	1.50 lbs
FOR301024	3-1/2"	15'	0.120"	3.260"	1.50 lbs
FOR301003	4"	20'	0.120"	3.750"	1.72 lbs

Line Control™ Whisker Poles

Line Control™ system simplifies the extension and retraction of whisker poles. Just unclench the line to extend or retract. Quick and easy with even the largest poles. Topping lift attachment points are standard on all poles.

Forespar® "Combo" Line Control™ Whisker poles offer all the same features as standard poles, but the Forespar® achieves significant weight savings by using an aluminum outer tube with a carbon fiber inner tube.



Part No.	Model No.	End Fittings	Recommended Mast Fittings	Collapsed Length	Max. Working Length	Tubing		Weight
						Diameters		
FOR401106	LC 10-18 EL-UXP	EL-UXP	PE-35C, RC-125, FC-125	121.75"	218.13"	2" & 2-1/2"		17 lbs
FOR401107	LC 10-18 EL-UTR	EL-UTR	PE-35C, RC-125, FC-125	121.75"	218.13"	2" & 2-1/2"		17 lbs
FOR402200	LC 12-22 UXP-UTR	UXP-UTR	RC-125, FC-125	148.50"	265.25"	2-1/2" & 3"		27 lbs
FOR402201	LC 12-22 UXP-UTR	UTS-UTR	T-125, AT-125	148.50"	265.25"	2-1/2" & 3"		28 lbs
FOR800802	LC 12-22 UTS-UTR CARBON FIBER	UTS-UTR	T-125, AT-125	148.50"	265.25"	2-1/2" & 3"		19 lbs
FOR402203	LC 12-22 COMBO	UTS-UTR	T-125, AT-125	148.50"	265.25"	2-1/2" & 3"		24 lbs
FOR403200	LC 13-24 UXP-UXP	UXP-UXP	RC-125, FC-125	162.00"	272.00"	3" & 3-1/2"		38 lbs
FOR403202	LC 13-24 UTS-UTR	UTS-UTR	T-125-S	162.00"	272.00"	3" & 3-1/2"		39 lbs
FOR800800	LC 13-24 UTS-UTR CARBON FIBER	UTS-UTR	T-125, AT-125	162.00"	272.00"	3" & 3-1/2"		24 lbs
FOR403203	LC 13-24 COMBO	UTS-UTR	T-125, AT-125	162.00"	272.00"	3" & 3-1/2"		34 lbs
FOR405200	LC 15-27 UTS-UXP	UTS-UXP	T-125-S	182.00"	324.00"	3-1/2" & 4"		58 lbs
FOR405201	LC 15-27 UTS-UTR	UTS-UTR	T-125-S	182.00"	324.00"	3-1/2" & 4"		58 lbs
FOR800801	LC 15-27 UTS-UTR CARBON FIBER	UTS-UTR	T-125, AT-125	182.00"	324.00"	3-1/2" & 4"		32 lbs
FOR405203	LC 15-27 COMBO	UTS-UTR	T-125, AT-125	182.00"	324.00"	3-1/2" & 4"		42 lbs



Small Boat Spinnaker Pole Kits

One end is installed with the other end loose so pole can be cut to desired length and completed in the field. Kits include nylon latching end fittings, nylon lanyard, part eye and hook kit



Part No.	Model No.	O.D.	Max Length	Shipping Weight
FOR303600	Mini-6	1"	6'	4 lbs
FOR303700	Mini-7	1-1/4"	7'	4-1/2 lbs

Standard Spinnaker Poles

All standard poles are supplied with double bridle topping lift/foreguy system. Unless otherwise specified, all poles are supplied jaws up.

Part No.	O.D.	End Fittings	Max Length	Shipping Weight
FOR304100	1-1/2"	UXP - UXP	7' 8"	6 lbs
FOR304101	2"	UXP - UXP	9' 6"	10 lbs
FOR304102	2"	UXP - UXP	9' 6"	10 lbs
FOR304103	2"	UTR - UTR	9' 6"	10 lbs
FOR304104	2-1/2"	UXP - UXP	11' 6"	14 lbs
FOR304105	2-1/2"	UTR - UXP	11' 6"	15 lbs
FOR304106	2-1/2"	UTR - UTR	11' 6"	15 lbs
FOR304107	3"	UXP - UXP	13' 6"	18 lbs
FOR304108	3"	UTR - UXP	13' 6"	19 lbs
FOR304109	3"	UTR - UTR	13' 6"	19 lbs
FOR304110	3-1/2"	UXP - UXP	15' 5"	33 lbs
FOR304111	3-1/2"	UTR - UXR	15' 5"	33 lbs
FOR304112	3-1/2"	UTR - UTR	15' 5"	34 lbs

Offshore Spinnaker Poles

Please specify end-for-end or single topping lift attachment.

Part No.	O.D.	End Fittings	Max Length	Shipping Weight
FOR304115	3"	UTS - UTR	13' 5"	18 lbs
FOR304116	3"	UTS - UGPS	13' 5"	19 lbs
FOR304117	3-1/2"	UTS - UTR	15'	33 lbs
FOR304118	3-1/2"	UTS - UGPS	15'	34 lbs
FOR304119	4"	UTS - UGPS	18' 5"	44 lbs
FOR304120	4-1/2"	UTS - UGPS	20' 5"	49 lbs

Carbon Fiber Spinnaker Poles



Forespar® carbon poles are made from pressure-cured intermediate modulus carbon fiber and high performance epoxy resin systems.

Poles come "Jaws Up" with * Double Bridle, or ** Custom Single Bridle.

Part No.	O.D.	End Fittings	Max Length	Weight
FOR800901*	2.0"	UXP - UXP	10.0'	4 lbs
FOR800101*	2.5"	UXP - UXP	12.0'	4.5 lbs
FOR800102*	2.5"	UTR - UTR	12.0'	4.5 lbs
FOR800201*	3.0"	UXP - UXP	14.0'	8 lbs
FOR800202*	3.0"	UTR - UTR	14.0'	8 lbs
FOR800203*	3.0"	UTS - UTR	14.0'	9.5 lbs
FOR800304**	3.5"	UTS - UGPS	16.5'	14 lbs
FOR800405**	4.0"	UTS - UGPS	18.5'	21 lbs
FOR800501**	4.5"	UTS - GP	22.5'	25 lbs
FOR800503**	4.5"	UTS - UGPS	22.5'	26 lbs

Forespar Ultra Series™ End Fittings

Composite end fittings are designed to be durable, high strength, light weight and corrosion resistant. Max. LOA boat outboard end - 43'; Max. LOA boat inboard end - 36'. Spectra™ trip line with terminal eye strap included.

All Ultra ends require minimum 1-1/2" inner diameter mast rings. Undersized rings will damage ends and void warranty.

UTR Style - Internal Trip

Part No.	O.D.	I.D.	End Fitting Length	End Fitting Weight
FOR304060	2.0"	1.870"	2.750"	6.97 oz
FOR304061	2.5"	2.334"	3.125"	9.25 oz
FOR304062	3.0"	2.835"	3.000"	11.92 oz
FOR304063	3.5"	3.260"	3.625"	15.72 oz



UXP Style - External Trip

Part No.	O.D.	I.D.	End Fitting Length	End Fitting Weight
FOR304054	1.5"	1.370"	2.750"	6.97 oz
FOR304050	2.0"	1.870"	1.870"	6.97 oz
FOR304051	2.5"	2.334"	3.125"	9.25 oz
FOR304052	3.0"	2.835"	3.000"	11.92 oz
FOR304053	3.5"	3.260"	3.625"	15.72 oz



Forespar Offshore Series GP & Ultra Series™ GPS End Fittings

Deluxe ocean racing end fittings featuring a wide flared throat and spring loaded trigger piston. All GP and UGPS fittings are for outboard use only, and will not work with mast cars. Internal trip only.

UGPS Style - Internal Trip

Part No.	O.D.	I.D.	End Fitting Length	End Fitting Weight
FOR304021	3.0"	2.835"	5.00"	38 oz
FOR304022	3.5"	3.260"	5.625"	41 oz
FOR304023	4.0"	3.750"	5.625"	48 oz
FOR304024	4.5"	4.260"	5.1875"	51 oz



GP Style - Internal Trip

Part No.	O.D.	I.D.	End Fitting Length	End Fitting Weight
FOR309030	3.0"	2.835"	5.00"	44 oz
FOR309033	3.5"	3.260"	5.625"	54 oz
FOR309035	4.0"	3.750"	5.625"	62 oz
FOR309038	4.5"	4.260"	5.1875"	77 oz



TS & UTS Style - Socket Ends

Part No.	Type	O.D.	I.D.	Weight
FOR309028	Aluminum	3.0"	2.835"	26 oz
FOR304080	Ultra	3.0"	2.835"	20 oz
FOR309031	Aluminum	3.5"	3.260"	29 oz
FOR304081	Ultra	3.5"	3.260"	23 oz
FOR405006	Aluminum	4.0"	3.750"	34 oz
FOR309036	Aluminum	4.5"	4.260"	45 oz
FOR304082	Ultra	4.0"	3.750"	23 oz



Mast Pad-Eyes



Part No.	Description
A	FOR400001 Flat base, measures 2-3/4" x 2". 1-5/8" ID.
B	FOR400002 Curved base, measures 2-3/4" x 2". 1-5/8" ID.
C	FOR400012 Flat base, heavy duty, measures 2-3/4" x 2". 1-5/8" ID.
D	RF30 Curved base, fits 2-3/8" dia. masts. 1-3/16" ID.
E	RF41 Curved base, fits 3-1/8" dia. masts. 1-3/4" ID.
F	RF602 Curved base, fits 2-3/8" dia. masts. 1-3/8" ID.